SEAL EXPANSION JOINT

Floor to Floor to Wall | Wall to Wall

25 - 75 mm (1 - 3") Expansion Gaps

Flexatec 1200 : A01



Features

Surface

Ribbed surface for improved slip resistance

Americans with Disabilities Act (ADA) compliant across the entire movement cycle

Movement

Good movement capacity

ASTM E-1399 Class I: Thermal
Class II: Wind

Traffic Frequency per day

> 25,000	-	≤ 10	> 25,000	-

System Options

Gap width(s)	25, 50, 75 mm
Height(s)	55, 64 mm
Metal type(s):	None
Colour(s)	Black (RAL 7021) coloured seal
Fire barrier	120-240 minutes
Waterproofing	Not applicable
Pre-assembly in factory	Contact Vexcolt

ADA COMPLIANT
ACCESS FOR ALL

APPLICATIONS

Airport Terminals | Educational | Exhibition Centres
Department Stores | Distribution & Retail Warehouses
Factories | Hospitals | Museums | Offices & Hotels
Parking | Places of Worship | Residential Buildings
Rail, Metros & Elevated Rail Stations | Roads & Bridges
Shopping Centres | Sports Stadiums | Supermarkets

www.vexcoltindia.com

VEXCOLT

| United Kingdom | T : +44 (0) 3707 876 543 | E : info@vexcolt.com | W : www.vexcolt.com
| India | T : +91 9599 291 000 | E : info@vexcoltindia.com | W : www.vexcoltindia.com

SEAL EXPANSION JOINT

Floor to Floor to Wall | Wall to Wall

25 - 75 mm (1 - 3") Expansion Gaps

Flexatec 1200 : A01

Expansion Joint Selection Criteria Load Rating **Product Details**

Joint Location	Gap Width B (mm)	Movement Capacity (mm) ±	[Total]	Eurocode Rating				Product Dimensions Height H1 (mm)	Height H2 (mm)	Sightline A (mm)	Blockout C (mm)	Product Number
Floor - Floor Floor - Wall Wall - Wall	25	± 7	[15]	-	31 kN	30 kN	-	55	-	25	-	1200-A01-025
	50	± 15	[30]					64		50		1200-A01-050
	75	± 25	[50]							75		1200-A01-075



VEXCOLT

| United Kingdom | T : +44 (0) 3707 876 543 | E : info@vexcolt.com | W : www.vexcolt.com

| India | T : +91 9599 291 000 | E : info@vexcoltindia.com | W : www.vexcoltindia.com