SLIMLINE EXPANSION JOINT

Floor to Floor

12 - 25 mm (1/2 - 1") Expansion Gaps

Intratec 060 : A01

Features

Surface

Discrete narrow profile

Hairline serrated surface for improved slip resistance

Easy transit: Americans with Disabilities Act (ADA) compliant across the entire movement cycle

Movement

Excellent movement capacity for profile width

ASTM E-1399 Class I: Thermal

Class II: Wind

Traffic Frequency per day

≤ 10,000	≤ 100	≤ 100	≤ 100	≤ 10

System Options

Gap width(s)	12, 25 mm
Height(s)	25, 35, 50 mm
Metal type(s)	6063 T5 & T6 Aluminium
Seal colour(s)	
Fire barrier	120-240 minutes
Waterproofing	Moisture barrier
Pre-assembly in factory	Contact Vexcolt

CENTRE SUPPORTED ADA COMPLIANT ACCESS FOR ALL

APPLICATIONS

Airport Terminals | Educational | Exhibition Centres
Department Stores | Distribution & Retail Warehouses
Factories | Hospitals | Museums | Offices & Hotels
Parking | Places of Worship | Residential Buildings
Rail, Metros & Elevated Rail Stations | Roads & Bridges
Shopping Centres | Sports Stadiums | Supermarkets

www.vexcoltindia.com

VEXCOLT

| United Kingdom | T : +44 (0) 3707 876 543 | E : info@vexcolt.com | W : www.vexcolt.com
| India | T : +91 9599 291 000 | E : info@vexcoltindia.com | W : www.vexcoltindia.com

SLIMLINE EXPANSION JOINT

Floor to Floor

12 - 25 mm (1/2 - 1") Expansion Gaps

Intratec 060 : A01

Expansion Joint Selection Criteria Load Rating **Product Details**

Joint Location	Gap Width B (mm)	Movement Capacity (mm) ±	[Total]	Eurocode Rating				Product Dimensions Height H1 (mm)	H2 (mm)	Sightline A (mm)	Blockout C (mm)	Product Number
Floor - Floor	12	± 2.5	[5.0]	5 kN	31 kN	30 kN	120 kN	25: 35: 50	-	20	120	060-A01-012-(H1)
	25	± 5.0	[10.0]				-			32	132	060-A01-025-(H1)

When specifying or ordering please add the **height (H1)** required to the Product Reference.
For example Intratec : 060-A01-025-050 denotes an expansion joint 50mm high.



VEXCOLT

I United Kingdom I T : +44 (0) 3707 876 543 I E : info@vexcolt.com I W : www.vexcolt.com
I India I T : +91 9599 291 000 I E : info@vexcoltindia.com I W : www.vexcoltindia.com