SINGLE-SEAL EXPANSION JOINT

Wall to Wall | Corner Wall

30 - 75 mm (1 1/4 - 3") Expansion Gaps

Maxatec 120 : A07-A09

Features

Surface

Smooth surface

Movement

Good movement capacity

ASTM E-1399 Class I: Thermal

Class II: Wind

Traffic Frequency per day

-	-	-	-	-

System Options

Gap width(s)	30, 50, 75 mm
Height(s)	14 mm
Metal type(s)	6063 T5 & T6 Aluminium
Seal colour(s)	Black (RAL 7021) Grey (RAL 7038) Beige (RAL 1015)
Fire barrier	120-240 minutes
Waterproofing	Moisture barrier
Pre-assembly in factory	Contact Vexcolt

APPLICATIONS

Airport Terminals | Educational | Exhibition Centres
Department Stores | Distribution & Retail Warehouses
Factories | Hospitals | Museums | Offices & Hotels
Parking | Places of Worship | Residential Buildings
Rail, Metros & Elevated Rail Stations | Roads & Bridges
Shopping Centres | Sports Stadiums | Supermarkets

www.vexcoltindia.com

VEXCOLT

| United Kingdom | T : +44 (0) 3707 876 543 | E : info@vexcolt.com | W : www.vexcolt.com
| India | T : +91 9599 291 000 | E : info@vexcoltindia.com | W : www.vexcoltindia.com

SINGLE-SEAL EXPANSION JOINT

Wall to Wall | Corner Wall

30 - 75 mm (1 1/4 - 3") Expansion Gaps

Maxatec 120 : A07-A09

Expansion Joint Selection Criteria Load Rating **Product Details**

Joint Location	Gap Width B (mm)	Movement Capacity (mm) ±	[Total]	Eurocode Rating				Product Dimensions Height H1 (mm)	H2 (mm)	Sightline A (mm)	Blockout C (mm)	Product Number
Wall - Wall	30	± 5	[10]	-	-	-	-	14	-	160	40	120-A07-030
	50	± 10	[20]							191	71	120-A07-050
	75	± 15	[30]							213	93	120-A07-075
Corner Wall	30	± 5	[10]	-	-	-	-	14	50	100	40	120-A09-030
	50	± 10	[20]							131	71	120-A09-050
	75	± 15	[30]							153	93	120-A09-075

Maxatec 120 : A07



Maxatec 120 : A09



VEXCOLT

| United Kingdom | T : +44 (0) 3707 876 543 | E : info@vexcolt.com | W : www.vexcolt.com

| India | T : +91 9599 291 000 | E : info@vexcoltindia.com | W : www.vexcoltindia.com