SEISMIC EXPANSION JOINT

Floor to Floor | Floor to Wall

50 - 500 mm (2 - 20") Expansion Gaps

Seismatec 420 : A01-A02

Features

Surface

Smooth transit central pan system

Movement

Seismic movement capacity

ASTM E-1399	Class I:	Thermal
	Class II:	Wind
	Class III:	Seismic

Thermal & Wind movement: +/-50mm

Seismic movement: +/-50% of expansion gap width

Traffic Frequency per day

> 25,000	≤ 1,000	≤ 1,000	≤ 100	-

System Options

Gap width(s)	50, 75, 100, 150, 200, 250, 300, 400, 500 mm
Height(s)	50, 60 mm
Metal type(s)	6063 T5 & 6063 T6 aluminium
Seal colour(s)	NA
Fire barrier	120-240 minutes
Waterproofing	Waterproofing membrane
Pre-assembly in factory	Contact Vexcolt

APPLICATIONS

Airport Terminals | Educational | Exhibition Centres
Department Stores | Distribution & Retail Warehouses
Factories | Hospitals | Museums | Offices & Hotels
Parking | Places of Worship | Residential Buildings
Rail, Metros & Elevated Rail Stations | Roads & Bridges
Shopping Centres | Sports Stadiums | Supermarkets

www.vexcoltindia.com

VEXCOLT

| United Kingdom | T : +44 (0) 3707 876 543 | E : info@vexcolt.com | W : www.vexcolt.com
| India | T : +91 9599 291 000 | E : info@vexcoltindia.com | W : www.vexcoltindia.com

Seismatec 420 : A01-A02

Expansion Joint Selection Criteria

Load Rating

Product Details

Joint Location	Gap Width B (mm)	Movement Capacity (mm) Thermal ±	Thermal [Total]	Seismic ±	Seismic [Total]	Eurocode Rating				Product Dimensions Height H1 (mm)	Height H2 (mm)	Sightline A (mm)	Blockout C (mm)	Product Number
Floor - Floor	50	± 50	[100]	+50/-35	[85]	20 kN	69 kN	30 kN		50: 60	-	119	611	420-A01-050-(H1)
	75			±50.0	[100]								636	420-A01-075-(H1)
	100			±50.0	[100]								661	420-A01-100-(H1)
	150			±75.0	[150]								711	420-A01-150-(H1)
	200			±100	[200]	10 kN	46 kN						761	420-A01-200-(H1)
	250			±125	[250]								811	420-A01-250-(H1)
	300			±150	[300]								861	420-A01-300-(H1)
	400			±200	[400]	5 kN	36 kN						1061	420-A01-400-(H1)
	500			±250	[500]								1191	420-A01-500-(H1)
Floor - Wall	50	± 50	[100]	±50.0	[100]	20 kN	69 kN	30 kN		50: 60	66	194	417	420-A02-050-(H1)
	75			±50.0	[100]								490	420-A02-075-(H1)
	100			±50.0	[100]								500	420-A02-100-(H1)
	150			±75.0	[150]								550	420-A02-150-(H1)
	200			±100	[200]	10 kN	46 kN						631	420-A02-200-(H1)
	250			±125	[250]								706	420-A02-250-(H1)
	300			±150	[300]								781	420-A02-300-(H1)
	400			±200	[400]	5 kN	36 kN						931	420-A02-400-(H1)
	500			±250	[500]								1081	420-A02-500-(H1)

a. 50mm deep systems are only suitable for the installation of 10mm deep paving within the central pan

b. 60mm deep systems are suitable for the installation of paving up to 20mm deep within the central pan

Seismatec 420 : A01



Seismatec 420 : A02